NREV





Rev Macchine

+39 0541 928 474 ☐ info@rev.it ⊠

www.rev.it

Compact and manoeuvrable self-propelled unit, equipped with jaw crusher, with hydraulic automatic adjustment and jaw opening control. Specially designed for medium and small sized construction sites, where a large feed mouth, excellent production and easy, fast maintenance are also required. quick maintenance.

The machine, fully hydraulic, is equipped with load-sensing pumps and a latest-generation electronic turbocharged motor latest generation. A machine with immediate controls, extreme ease of use and maintenance.

Jaw crusher	
Inlet dimensions (mm)	1015x650
CSS adjustment (mm)	30-120
Weight (kg)	16500
Feeding hopper	
Standard capcity (m3)	3
Feed hight (m)	3,4
Apron feeder	
Width (mm)	900
Length (mm)	2700
Main conveyor	
Width (mm)	800
Discharge height (mm)	3100
Side discharge conveyor	
Width (mm)	500
Discharge height (mm)	2150
Engine	CAT Stage V
Power (kW)	151
Crawler tread widht	
Wheel base (mm)	3315
Weight (kg)	29900 31190
Performance	
Max feeding size (mm)	500-600
Hourly production ton/h	60-180
Working dimensions	
Length (mm)	12940
Width (mm)	4625
Height (mm)	3400

- Optionals:

 √ Return or stockpile conveyor

 √ Dust suppression system

 √ Hopper oversizes

 √ Automatic greasing unit


 √ Under crusher discharge plate





Transport dimensions

Length (mm)	12940
Width (mm)	2550
Height (mm)	3400
Weight (kg)	29900



Larghezza di trasporto 2550



Rev Macchine

+39 0541 928 474 info@rev.it ⊠