





Rev Macchine +39 0541 928 474 info@rev.it www.rev.it () Rising landfill costs and raw material prices, along with the necessity to separate waste, make recycling and sorting building materials not only environmentally necessary, but also cost-effective for construction companies. Mobile crushers enable profitable recycling of asphalt, concrete, and demolition debris, as well as the processing of natural stone. The GCV70.92 compact mobile crusher offers excellent mobility and a high degree of user-friendliness due to its numerous technological features. Versatile adjustment options ensure high-quality final grain and increased usability.

Inlet dimensions (mm)	900 x 720
Blow bars	4
CSS adjustment (mm)	20-110
Feeding hopper	
Standard capacity (m3)	4
Feed height (m)	3200
Vibrating feeder Grizzly	
Width (mm)	900
Length (mm)	3500
Main conveyor	
Width (mm)	1000
Discharge height (mm)	3200
Side discharge conveyor	
Width (mm)	500
Discharge height (mm)	2300
Engine	Volvo
Power (kW)	210
Track	400
Wheel base (mm)	2900
Performance	
Max feeding size (mm)	550
Hourly production ton/h	240 Ton/h
Working dimensions	
Length (mm)	11600
Width (mm)	2500
Height (mm)	3200

- Optional: √ Side conveyor √ Dust suppression system √ Automatic greasing system





Rev Macchine

+39 0541 928 474 [info@rev.it 🖂

www.rev.it 🕀

Transport dimensions	
with screen	

Length (mm)	9600
Width (mm)	2500
Height (mm)	3200
Weight (kg)	25500

